



TECHNICAL DATA			Pump type NDP-80BPT		
Air supply pressure	0,2-0,7	MPa	Max. viscosity (neg. suc.)	10.000	Cp
Max. discharge volume/cycle	3800	Cc	Max. viscosity (flooded suction.)	30.000	Cp
Max. discharge volume	580	L/min	Max. air consumption	6000	NL/min
Max. discharge pressure	0,7	MPa	Max. noise level	82	dB(a)
Max. size of solids	10	mm	Operating temp. ambient	70	°C
Max. suction lift dry	PTFE fitted	4,5	Max operating temp. fluid		
Max. suction lift wet	PTFE fitted	8,2	Diaphragm compound		
Max. fluid inlet pressure	PTFE fitted	0,03	Diaphragm compound	PTFE	82 °C
Max. suction lift dry	Rubber fitted		Diaphragm compound		
Max. suction lift wet	Rubber fitted				
Max. fluid inlet pressure	Rubber fitted		Net Weight	Type P	PPG
		MPa			70,0 Kg
Caution! Data based on water (1 Cp)					
Wetted parts: Pump chambers + manifolds			PPG - Polypropylene reinforced with glass fiber		
Motor			ADC12 - Aluminum (PTFE COATING AVAILABLE)		

