

IWAKI
MAGNETIC
DRIVE
PUMPS

MXM





Better withstanding difficult operating conditions


The proven non-contact system and self-radiating bearing structure deliver substantial improvements in tolerance of dry running and poor suction conditions.

Non contact system

Unlike conventional magnetic drive pumps, the MXM series are designed to prevent contact between the bearing and the rear thrust faces, even during dry running. By preventing contact, the rear thrust ring minimizes heat generation to prevent melting of plastic parts.

Self radiation structure (PAT.)

Through heat-dispersion holes provided in the fixed portions of the impeller and the magnet capsule, the liquid around the spindle and the bearing is forced to circulate so that heat generated by sliding can be reduced effectively. Thus, thermal deformation and melt are prevented.



Magnetic drive pumps with an excellent balance of features and performance

The MXM series of pumps have now been added to the line-up of Iwaki's magnetic drive process pumps, which have earned high acclaim and the trust of users all around the world. The new MXM series feature an excellent balance of the characteristics required of chemical pumps, including corrosion resistance, durability and safety. They employ a non-contact, self-radiating bearing structure to better withstand difficult operating conditions. The advent of the MXM series has further expanded the array of choices offered by Iwaki's process magnetic drive pumps.

Exceptional corrosion resistance

The MXM series employ optimum anti-corrosive materials such as carbon fiber reinforced ETFE (CFRETFE), high quality ceramic and carbon for parts that come in contact with liquid. The most suitable impeller size and motor output can be selected for the required liquid property.



Impeller+Magnet capsule



Spindle+Bearing

Robust structure

The pumps have an external armour of high strength ductile cast iron for use in heavy duty chemical process applications. The sealing performance between the front casing and the rear casing is drastically enhanced by our original structure (patent pending), offering high reliability.



Cover+Front casing

Enhanced safety

The MXM features a unique rear casing shape designed to prevent stress concentration. This increases both the pump's pressure resistance and the mechanical strength of the spindle support. The high temperature model uses a dual structure incorporating an FRP rear casing cover. In addition to further increasing the pump's pressure resistance, it improves safety with dual containment preventing liquid leakage in the event of unexpected damage to the rear casing.



Rear casing+Rear casing cover (Option)



MXM545



MXM542



Specifications (50Hz)

Model	Pump size Suction × Discharge	Impeller size	Capacity L/min	Head m
MXM22 (Impeller range 1)	25mm × 25mm	100	150	7.5
		090	150	5.5
		070	150	2.5
MXM22 (Impeller range 2)		105	150	8
MXM44 (Impeller range 1)	40mm × 40mm	115	200	9.5
		110	200	8
		100	200	6
		090	200	5
MXM44 (Impeller range 2)		130	200	12
MXM54 (Impeller range 1)	50mm × 40mm	150	200	18.5
		140	200	17
		120	200	13.5
		150	300	20
MXM54 (Impeller range 3)		140	300	18.5
		130	300	16.5
		110	300	10.5
		150	400	25
MXM54 (Impeller range 4)		140	400	20.5
		125	400	15.5
		110	400	9.5

Note1: Liquid temp. range

Standard: -10 to 90 °C High temp. version (with rear casing cover): -10 to 105 °C (10 to 105 °C when AFLAS* O ring is used)


Note2: Max operating pressure

Standard MXM22: 0.2MPa, MXM44: 0.3MPa, MXM54: 0.45MPa High temp. version (with rear casing cover): 0.7MPa


Construction and materials

Part	Material code	CF	FF	KK
1 Front casing	CFRETFE			
2 Rear casing				
3 Impeller				
4 Magnet capsule				
5 Spindle	High-purity alumina ceramic	High-density carbon	High-purity alumina ceramic	SiC
6 Bearing	High-density carbon			
7 Liner ring	High-purity alumina ceramic			
8 Mouth ring	PTFE with filler			
9 Rear thrust	MXM22/44: CFRETFE, MXM54: CFRPFA			
10 O ring	FKM/EPDM/AFLAS®/ DAI-EL PERFLUORO®			
11 Lock pin	Note	CFRETFE		






Note: 54 type only



Pump identification




Performance curves




· The shaft power curves shown above are calculated by using our standard test motor. Contact us for detail.

Dimensions in mm

Without base



With base



Without base

Model	(H)	(L)	A	B	a	(b)	c	(d)	e	f	g	h	i
MXM220-H	237	475	25A	25A	110	150	51	95	165	115	122	88	4-ø12
MXM221-H		470											
MXM441-H	275	498	40A	40A	130	170	58	113	250	135	140	106	4-ø14
MXM442-H		535											
MXM542-H		467											
MXM543-H	295	489	40A	50A	140	180	65	106	275	155	140	87	4-ø14
MXM545-H		594											

With base

Model	(W)	(H)	(L)	A	B	a	c	d	e	f	g	h	i	j
MXM220-H			475											
MXM221-H	300	317	470	25A	25A	250	51	130	220	195	122	88	4-ø19	450
MXM441-H			498											
MXM442-H	350	365	535	40A	40A	300	58	130	260	225	140	106	4-ø19	489
MXM542-H			467											
MXM543-H	400	385	489	40A	50A	350	65	140	480	245	140	87	4-ø19	735
MXM545-H			594											

Notes for selection

(1) The performance curves in this catalogue represent the data measured using clear water at 20 °C.

(2) Choose the pump model suited to the liquid gravity.

Make sure that the motor output is ten percent higher than theoretically required.

Shaft power (Sp) × liquid gravity × 1.1 < Motor output

(Note) The shaft power (Sp) increases in proportion to the liquid gravity.

As the viscosity rises, the shaft power is higher while the head and the discharge are lower.

The power and the performance need to be adjusted.

(3) No magnetic drive pump supports continuous closed running. Be sure to ensure the minimum flow volume.

• Minimum flow volume

MXM22/44 : 10 L/min.

MXM54 Impeller range 1, 2 and 3 : 20 L/min.

Impeller range 4 : 50 L/min.

(4) The pressure resistance of the pump is as follows.

Be sure to ensure that the internal pressure of the pump does not exceed the value specified below.

• Standard model -10 °C to 90 °C (without rear casing cover)

MXM22: 0.2MPa, MXM44: 0.3MPa, MXM54: 0.45MPa

• High temperature version -10 °C to 105 °C (with rear casing cover)

: 0.7MPa

(5) FF material models

• Liquid should be 1m Pa·s (cP) or more.

• HQ performance is somewhat different from CF/KK models. If you need to know the detail, please contact with us.

(6) Deliberate prolonged dry running or entrained air operation is not recommended.

• The CF type has a degree of tolerance to dry running and operation with entrained air in the liquid.

• The KK type has the same degree of tolerance as the CF type under operation with entrained air in the liquid, but not allowed to run dry.

• The FF type is not allowed to run dry or operation with entrained air.

Optional accessories

Iwaki pump protector DRN series

Detects unusual pump operating conditions including dry-running and overload

The DRN model protects equipment (including pumps) from damage!

Minimizes production downtime.

Identifies possible causes of alarms so they can be investigated and addressed.

Multiple Input	Two analog, one digital, one temperature input and one current input
Easy operation	Equipped with EASY setup mode to remember the operation status and set the lower/upper limit values, as well as AUTO setup mode
Bar graph	Visible indication of current operating status
Logging capability	Data log feature for preventative maintenance scheduling
Communication	RS485 external communication capability




Specifications

Model	DRN-01	DRN-02
Amperometric range	0.5-30.00A	5.0-200.0A
Unit's source voltage	AC100-240V 50Hz 10VA	
Operating temperature	0-40°C	
Operating humidity	35-85%RH	

IWAKI Process Magnetic Drive Pump Series

MDW SERIES

The world largest-class
fluoroplastic magnetic drive pump



Specifications

- Max. discharge capacity: 300 m³/hr
- Max. head: 98 m
- Main materials: ETFE, PFA
- Liquid temp. range: -10 to 105 °C (ETFE)
-10 to 120 °C (PFA)

MDE SERIES

The most reliable,
large-sized magnetic drive pump
designed for process use



Specifications

- Max. discharge capacity: 240 m³/hr
- Max. head: 55 m
- Main materials: ETFE, PFA
- Liquid temp. range: 0 to 100 °C

MDM SERIES

Magnetic drive process pumps
with dry running capability



Specifications

- Max. discharge capacity: 84 m³/hr
- Max. head: 74 m
- Main materials: CFRETFE, PFA
- Liquid temp. range: -20 to 105 °C (CFRETFE)
-20 to 150 °C (PFA)

MX/MX-F SERIES

Withstands difficult operating conditions
and offers high efficiency



Specifications

- Max. discharge capacity: 30.6 m³/hr
- Max. head: 35 m
- Main materials: GFRPP, CFRETFE
- Liquid temp. range: 0 to 80 °C

SMX/SMX-F SERIES

Versatile self-priming magnetic drive pump with
enhanced durability under abnormal operation



Specifications

- Max. discharge capacity: 26.4 m³/hr
- Max. head: 25.5 m
- Main materials: GFRPP, CFRETFE
- Liquid temp. range: 0 to 80 °C

IWAKI CO., LTD. 6-6 Kanda-Sudacho 2-chome Chiyoda-ku Tokyo 101-8558 Japan TEL : (81)3 3254 2935 FAX : 3 3252 8892

IWAKI has global net work.
Please find your distributor location at

www.iwakipumps.jp

European office : IWAKI Europe GmbH
Germany : IWAKI Europe GmbH
Holland : IWAKI Europe GmbH (Netherlands Branch)
Italy : IWAKI Europe GmbH (Italy Branch)
Spain : IWAKI Europe GmbH (Spain Branch)
Belgium : IWAKI Belgium N.V.
Denmark : IWAKI Nordic A/S
Finland : IWAKI Suomi Oy
France : IWAKI France S.A.
Norway : IWAKI Norge AS
Sweden : IWAKI Sverige AB
U.K. : IWAKI Pumps (UK) Ltd.

TEL: (49)2154 9254 0 FAX: 2154 9254 48
TEL: (49)2154 9254 50 FAX: 2154 9254 55
TEL: (31)74 2420011 FAX: (49)2154 925448
TEL: (39)0444 371115 FAX: 0444 335350
TEL: (34)93 37 70 198 FAX: 93 47 40 991
TEL: (32)13 67 02 00 FAX: 13 67 20 30
TEL: (45)48 24 2345 FAX: 48 24 2346
TEL: (358)9 2745810 FAX: 9 2742715
TEL: (33)1 69 63 33 70 FAX: 1 64 49 92 73
TEL: (47)23 38 49 00 FAX: 23 38 49 01
TEL: (46)8 511 72900 FAX: 8 511 72922
TEL: (44)1743 231363 FAX: 1743 366507
() Country codes

U.S.A. : IWAKI America Inc.
Argentina : IWAKI America Inc. (Argentina Branch)
Brasil : IWAKI Do Brasil Comercio De Bombas Hidraulicas LTDA.
Singapore : IWAKI Singapore Pte Ltd.
Indonesia : IWAKI Singapore (Indonesia Office)
Malaysia : IWAKIm Sdn. Bhd.
Australia : IWAKI Pumps Australia Pty Ltd.
Hong Kong : IWAKI Pumps Co., Ltd.
China : GFTZ IWAKI Engineering & Trading Co., Ltd.
Taiwan : IWAKI Pumps (Shanghai) Co., Ltd.
Thailand : IWAKI Korea Co., Ltd.
Vietnam : IWAKI Pumps Taiwan Co., Ltd.
Korea : IWAKI (Thailand) Co., Ltd.
Thailand : IWAKI Pumps Vietnam Co., Ltd.

TEL: (1)508 429 1440 FAX: 508 429 1386
TEL: (54)11 4745 4116 FAX: 19 3244 5900
TEL: (55)19 3244 5900 FAX: 6316 3221
TEL: (65)6316 2028 FAX: 21 6906612
TEL: (62)21 6906606 FAX: 3 7803 4800
TEL: (60)3 7803 8807 FAX: 2 9899 2421
TEL: (61)2 9899 2411 FAX: 2607 1000
TEL: (852)2607 1168 FAX: 20 84359181
TEL: (86)20 84350603 FAX: 21 6272 6929
TEL: (86)21 6272 7502 FAX: 2 2630 4801
TEL: (82)2 2630 4800 FAX: 2 8227 6818
TEL: (886)2 8227 6900 FAX: 2 322 2477
TEL: (66)2 322 2471 FAX: 613 933399
TEL: (84)613 933456 FAX: 613 933399

Caution for safety use:
Before use of pump, read instruction manual carefully to use the product correctly.

Legal attention related to export.

Our products and/or parts of products fall in the category of goods contained in control list of international regime for export control. Please be reminded that export license could be required when products are exported due to export control regulations of countries.

Actual pumps may differ from the photos. Specifications and dimensions are subject to change without prior notice. For further details please contact us.

The posting and copying from this catalogue without permission is not accepted firmly.